

FRONT-450-CNC+6 PUSHER AUTOPOS

DESCRIPTION

Fully automatic feeding and miter cutting saw -22,5°/-45°/90°/45°

CHARACTERISTICS

- Cutting at -22,5°/-45°/90°/45°
- 6 meter feeder CNC controlled
- 1 pneumatic vertical clamping cylinder
- 2 pneumatic horizontal clamping cylinders
- Twin pressure LOW/HIGH system for clamping security
- Adjustable cutting speed
- Pneumatic lubrication by venturi device
- Automatic feeding, cutting and angle turning
- Automatic Open/Closed Hood

OPTION

- Lubetools mist lubrication
- Automatic START/STOP of vacuum cleaner
- Blade speed inverter
- PERTINAX layer protection surface
- USB connection
- Label printer
- Barcode reader



CNC CONTROL



SPECIFICATIONS

Engine	3 HP
Diameter max. saw	450 mm (included)
Saw speed	2800 rpm
Dimensions	1000X1400X1800 mm
Weight	450 kg
Cutting capacity circular 90°	140 mm
Cutting capacity circular 45°	140 mm
Cutting capacity rectangular 90°	200X100 mm
Cutting capacity rectangular 45°	150X100 mm
Cutting capacity circular 22.5°	100 mm.
cutting capacity rectangular 22.5°	100X50 mm.

CUTTING DIAGRAM

